



China 608z Bearing Supplier



6207 Bearing 2D drawings and 3D CAD models

6207 6208 6209 6210 6211 6212 6213 6214 6215
 6216 6217 6218 Distributor of SKF NSK Timken
 Koyo NACHI NTN Bearing, Bearings, Ball
 Bearing, High Quality

Bearing No. 6207

| | |
|-------------------------------|--------------------------|
| Size | 35x72x17 mm |
| Bore Diameter | 35 mm |
| Outer Diameter | 72 mm |
| Width | 17 mm |
| d | 35 mm |
| D | 72 mm |
| B | 17 mm |
| C | 17 mm |
| r min. | 1.1 mm |
| da min. | 42 mm |
| Da max. | 65 mm |
| ra max. | 1.0 mm |
| Weight | 0.288 Kg |
| Basic dynamic load rating (C) | 25,7 kN |
| Basic static load rating (C0) | 15,3 kN |
| (Grease) Lubrication Speed | 9000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NACHI |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| Product Group | B00308 |
| Enclosure | Open |



China 608z Bearing Supplier

| | |
|---------------------------------|---|
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 35MM Bore; 72MM Outside Diameter; 17MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage |
| Other Features | Deep Groove |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nachiamerica.com |
| Outer Race Width | 0.669 Inch 17 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outside Diameter | 2.835 Inch 72 Millimeter |
| Bore | 1.378 Inch 35 Millimeter |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Bore Size | 35 mm |
| Width | 17 mm |
| Fillet Radius/Chamfer | 1.1 mm |
| | |



China 608z Bearing Supplier

| | |
|-------------------------|-------------------|
| Dynamic Load Rating | 25,700 N |
| Static Load Rating | 15,300 N |
| Limiting Speed - Grease | 9,800 rpm |
| Limiting Speed - Oil | 11,000 rpm |
| Factor f_0 | 13.8 |
| Radial Clearance | 0.006 to 0.020 mm |
| da (min) | 42 mm |
| Da (max) | 65 mm |
| ra (max) | 1 mm |