



China 608z Bearing Supplier



6212 Bearing 2D drawings and 3D CAD models

SKF NACHI Scooter/Motorbike/Motorcycle Parts 6212 Deep Groove Ball Bearing

Bearing No. 6212

Size	60x110x22 mm
Bore Diameter	60 mm
Outer Diameter	110 mm
Width	22 mm
d	60 mm
D	110 mm
B	22 mm
C	22 mm
r min.	1.5 mm
da min.	69 mm
Da max.	101 mm
ra max.	1.5 mm
Weight	0.783 Kg
Basic dynamic load rating (C)	52,5 kN
Basic static load rating (C0)	36 kN
(Grease) Lubrication Speed	5800 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling	No



China 608z Bearing Supplier

Slot	
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	60MM Bore; 110MM Outside Diameter; 22MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nachiamerica.com
Outer Race Width	0.866 Inch 22 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	2.362 Inch 60 Millimeter
Outside Diameter	4.331 Inch 110 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	60 mm
Width	22 mm
Fillet Radius/Chamfer	1.5 mm
Dynamic Load Rating	52,500 N
Static Load Rating	36,000 N



China 608z Bearing Supplier

Limiting Speed - Grease	6,000 rpm
Limiting Speed - Oil	7,100 rpm
Factor f_0	14.3
Radial Clearance	0.008 to 0.028 mm
d_a (min)	69 mm
D_a (max)	101 mm
r_a (max)	1.5 mm